

ESSENTIAL HARNESS: STAINLESS STEEL

PART CODE: **H101SS**



**HEIGHT
SAFETY**

PRODUCT FEATURES >

- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment.
- High Tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation.
- Retro-Reflective Thread in webbing for improved visibility in low light.
- Large Dorsal D Ring for easier connection.
- Closed Loop Webbing system on rear Dorsal D maintains positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back of workers head.
- Extended Belay Loops make connection of hardware easier, also maintains absolute front and centre positioning as per AS/NZS requirements.
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker.
- Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap.
- 100% Stainless Steel Hardware for extended life in most corrosive environments.
- Service Pouch on back.

APPLICATIONS >

Fall Arrest, Construction, Ladder, Scaffolding, Warehouse, Corrosive Environments.

STANDARDS >



AS/NZS 1891.1:2007
BMP 713822
BMP 713823
Australian Standard



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

AUS: 1300 546 747

NZ: 0800 546 747

INTERNATIONAL: +61 1300 546 747

WWW.LINQHS.COM

ESSENTIAL HARNESS: STAINLESS STEEL

PART CODE: **H101SS**



**HEIGHT
SAFETY**

PRODUCT DETAILS >


- AUS/NZ designed and engineered
- Size ranges available- Small, Standard (M-L) and Maxi (XL-2XL).
- 10 year life span from date of manufacture



**DORSAL
D RING**



**BUCKLE
CONNECTORS**



**RETRO
REFLECTIVE
THREAD**



TECHNICAL INFORMATION >

- **Webbing Material:** Polyester; 45mm; UV Resilient.
- **Buckle Material:** Corrosion resistant electrophoresis; 100% stainless steel.
- **Fall Arrest Hardware:** Drop Forged corrosion resistant electrophoresis; 100% stainless steel.
- **Thread:** Polyester; 9.81 Newtons (10kg); Extension at break 19.5%.
- **Stitch Pattern:** THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast.
- **Plastic Material:** UV stabilised high density polyethylene.
- **Weight:** 1.1kg
- **Web Tenacity:** Range: Min 28kN - Max 30kN.
- **Drop Forged D Rings:** 100% stainless steel: 40kN.
- **Buckle Strength:** 12 to 17kN model dependent; Laser etched or hard marked on buckle.
- **Padding Material:** Neoprene laminate.



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

AUS: 1300 546 747

NZ: 0800 546 747

INTERNATIONAL: +61 1300 546 747

WWW.LINQHS.COM